NC Job Risk Assessment

Name(s) of Risk Team Members: L. Davis, D. Elling, R. Sabatini	Point Value → Parameter ↓	1	2	3	4	5
	Frequency (B)	<once td="" year<=""><td><pre><pre><pre><pre><pre></pre></pre></pre></pre></pre></td><td><once td="" week<=""><td><once shift<="" td=""><td>>once/shift</td></once></td></once></td></once>	<pre><pre><pre><pre><pre></pre></pre></pre></pre></pre>	<once td="" week<=""><td><once shift<="" td=""><td>>once/shift</td></once></td></once>	<once shift<="" td=""><td>>once/shift</td></once>	>once/shift
Job Title: Cryogenic Work Job Number or Job Identifier: NC-JRA-005	Severity (C)	First Aid Only	Medical Treatment	Lost Time	Partial Disability	Death or Permanent Disability
Job Description: General work with non-combustible cryogenic fluids and systems. Does not include liquid hydrogen or liquid oxygen. Training and Procedure List (Optional): Approved By: R. Sabatini	Likelihood (D)	Extremely Unlikely	Unlikely	Possible	Probable	Multiple
Rev. #: 1 Stressors (if applicable, please list all):	Reason for Re	evision (if applicab	 ble):	Comments:		

							dditi rols	onal		After Additional Controls						
Job Step / Task	Hazard	Control(s)	Stressors Y/N	# of People A	Frequency B	Severity C	Likelihood D	Risk* AxBxCxD	Control(s) Added to Reduce Risk	Stressors Y/N	# of People A	Frequency B	Severity C	Likelihood D	Risk* AxBxCxD	% Risk Reduction
Moving storage vessel (dewar) to/from location	Overexertion injuries caused by excessive lifting, pushing, pulling, holding or carrying an object	Wheeled dewars, training, safety shoes	N	1	4	2	2	16								
	Being struck by object due to pressure release	Vessel design/certification, equipment inspection, training, Tier 1	N	1	1	2	1	2								
	Dewar tip over due to uneven surfaces	Dedicated transfer route	N	1	2	2	3	12								

NC Job Risk Assessment

						e Ad Cont		onal			A					
Job Step / Task	Hazard	Control(s)	Stressors Y/N	# of People A	Frequency B	Severity C	Likelihood D	Risk* AxBxCxD	Control(s) Added to Reduce Risk	Stressors Y/N	# of People A	Frequency B	Severity C	Likelihood D	Risk* AxBxCxD	% Risk Reduction
Connecting or disconnecting storage dewar to	Falls to lower level from ladders or other cryostat access	Dedicated Ladder, equipment inspection, Tier 1, training, procedures	N	1	3	3	3	27								
cryostat	Being struck by object due to pressure release	Vessel design/certification, equipment inspection, training, Tier 1	N	1	1	2	1	2								
	Contact with temperature extremes that result in such injuries frost bite or burns	Training, procedures, PPE, gloves, eye protection, proper clothing	N	1	3	2	3	18								
	Oxygen deficiency	Training, posting, safety reviews, ventilation, ODH calculations	N	2	4	5	1	40								
Pressurizing storage dewar	See "Work with Compressed gas" JRA	See working with compressed gases														
Transferring cryogenic liquid from storage	Being struck by object due to pressure release	Vessel design/certification, equipment inspection, training, Tier 1	N	1	1	2	1	2								
dewar to cryostat	Contact with temperature extremes that result in such injuries frost bite or burns, frozen o-ring	Training, procedures, gloves, eye protection, proper clothing	N	1	1	2	1	2								
	Oxygen deficiency	Training, posting, safety reviews, ventilation, ODH calculations	N	2	4	5	1	40								
	Auto-fill fa1ilure	Design, training, ODH calculations, procedure	N	1	1	5	1	5								

NC Job Risk Assessment

							dditi rols	onal			Α									
Job Step / Task	Hazard	Control(s)	Stressors Y/N	# of People A	Frequency B	Severity C	Likelihood D	Risk* AxBxCxD	Control(s) Added to Reduce Risk	Stressors Y/N	# of People A	Frequency B	Severity C	Likelihood D	Risk* AxBxCxD	% Risk Reduction				
Transferring cryogenic fluid to portable dewar, or system	Contact with temperature extremes that result in such injuries frost bite or burns	Training, procedures, gloves, eye protection, proper clothing	N	1	3	2	3	18												
	Oxygen deficiency	Training, posting, safety reviews, ventilation, ODH calculations	N	1	3	4	1	12												
Further Description of Controls Added to Reduce Risk:																				
*Risk:	0 to 20 Negligible	21 to 40 Acceptable		41 to 60 Moderate											81 or greater Intolerable					