



STELLA-II Experiment Update on Monoenergetic Laser Acceleration

Karl P. Kusche

ATF Users' Meeting
Jan. 31, 2002

Work was supported by the U.S. Department of Energy, Grant Nos. DE-FG03-98ER41061,
DE-AC02-98CH10886, and DE-FG03-92ER40695

STELLA Collaborators

- STELLA team consists of collaborators from several institutions
 - Marcus Babzien (BNL)
 - Ilan Ben-Zvi (BNL)
 - Lora Campbell (STI)
 - David Cline (UCLA)
 - Christian Dilley (STI)
 - Juan Gallardo (BNL)
 - Steve Gottschalk (STI)
 - Ping He (UCLA)
 - Karl Kusche (BNL)
 - Richard Pantell (Stanford U.)
 - Igor Pogorelsky (BNL)
 - David Quimby (STI)
 - John Skaritka (BNL)
 - Loren Steinhauer (UW)
 - Arie van Steenbergen (BNL)
 - Vitaly Yakimenko (BNL)
 - Feng Zhou (UCLA)
- Newest STELLA collaborators
 - Russian Academy of Sciences: Nikolai Andreev, Sergei Kuznetsov, and Alla Pogosova
 - Hebrew University: Arie Zigler
 - Naval Research Laboratory: Antonio Ting




Outline

- Introduction
- Staged Electron Laser Acceleration (STELLA-II)
 - Description of experiment
 - Present status
 - Near-term plans
- Results of Workshop on Staged Laser Acceleration, Dec. 4-6, 2001, Tucson, Arizona
- Closing remarks



STELLA Demonstrated Staging of Laser Acceleration Process

- Staging process demonstrated for first time during Staged Electron Laser Acceleration (STELLA) Experiment*
 - Used inverse free electron laser (IFEL) as laser acceleration mechanism
 - IFEL buncher (IFEL1) creates femtosecond microbunches
 - IFEL accelerator (IFEL2) accelerates microbunches



*W. D. Kimura, *et al.*, Phys. Rev. Lett. **86**, 4041-4043 (2001).

STELLA-II Builds Upon Success of STELLA

- Primary goal of STELLA-II is to demonstrate staged monoenergetic laser acceleration
- STELLA-II will be one of first to examine monoenergetic laser acceleration
 - Use single laser beam to drive both buncher and accelerator – greatly reduces phase jitter
 - Use tapered undulator in accelerator + high laser power (≥ 10 GW) – enables clean separation of accelerated microbunches while maintaining narrow energy spread

Model prediction at optimum phase delay


11% gap taper

$$P_L = 10 \text{ GW}$$


$$E = 46.5 \text{ MeV}$$

$$B_{\text{buncher}} = 250 \text{ G}$$


$$B_{\text{chicane}} = 6290 \text{ G}$$




Schematic of STELLA-II Experiment




Sketch of STELLA-II Beamline



STELLA-II Beamline and Baseplate




Undulator (Accelerator) on Beamline




Photograph of Buncher

- Single-period electromagnet
 - Purpose is to modulate e-beam energy by $\pm 0.5\%$
 - High laser power means little B-field needed
 - Features wide gap to accommodate short laser beam Rayleigh range



3-D Drawing of Chicane

- Hybrid electromagnet/permanent magnet device
- Serves two purposes
 - Permanent-magnet field chosen to cause bunching at accelerator (eliminates 2-m drift space between buncher and accelerator during STELLA)
 - Electromagnet allows fine adjustment of phase delay between arrival of microbunches and laser pulse in accelerator undulator (replaces optical delay plate used during STELLA)



STELLA-II Hardware Being Tested & Laser Transport Being Upgraded

- New beamline vacuum pipe and diagnostic ports installed
 - Located where STELLA-I IFEL1 (buncher) previously positioned
 - *E*-beam successfully tuned through new beamline
- Untapered and tapered undulator already tested individually
 - Plan to initially use 11% gap taper (one of highest tapers ever tested)
- Buncher and chicane need to be tested next
- Laser transport system being upgraded to permit delivering higher laser power
 - Need short Rayleigh range for high laser intensity in undulator and to prevent optical damage of optics
 - Laser beam to enter beamline through lid of Smith-Purcell chamber
 - Large diameter mirrors already available, other custom optics ordered, (NaCl window and lens)

Near-Term Plans

- Buncher installed on new beamline
 - Still need to verify proper operation
- Support hardware for new laser beam transport system currently being designed and should be fabricated by latter part of February
 - Optics should be delivered at same time
 - Assemble new laser beam transport system in February
- In February, finish assembly, testing, and installation at ATF of chicane
- Test new laser beam transport system together with individual STELLA-II components beginning in March
 - ATF CO₂ amplifier should be ready to deliver ≥ 10 GW
 - Finish individual testing of buncher and chicane
- Begin fully integrated experiments in March/April

Results of 2001 Workshop on Staged Laser Acceleration

- Purpose of STELLA 2001 Workshop
 - Examine issues related to performing STELLA-II experiment
 - Develop ideas for staging other laser acceleration methods, such as laser wakefield acceleration (LWFA)
 - Discuss related issues, such as plasma channels suitable for staging
 - Examine other new types of acceleration mechanisms, such as novel vacuum acceleration
- Workshop was very successful and productive
 - Experimental issues related to STELLA-II and vacuum acceleration discussed
 - LWFA experts (Andreev and Ting) provided valuable input on possible new staging ideas
- New collaborations more firmly established
 - Will use when developing ideas for next program following STELLA-II
 - Analysis already begun on several new ideas

Closing Remarks

- STELLA-II hardware coming into place nicely
 - Individual components tested thus far performing as expected
- Upgraded laser beam transport should enable delivering >4 J pulse energy
 - For 180 ps pulse length, corresponds to >20 GW
 - For ~10 ps pulse length, corresponds to 400 GW
- Monoenergetic laser acceleration can be demonstrated with only 10 GW
 - Plan to initially deliver ~10 GW
 - As higher peak power becomes available, can try larger taper
 - Maximum possible taper is $\approx 20\%$ and requires at least 100 GW
 - Buncher can handle 100's GW (requires less B-field)
 - Chicane performance is not directly tied to laser power
- Expect this early spring to be another exciting time for STELLA!