

# 7 DIRECT RADIATION: TLD PROGRAM

## CHAPTER CONTENTS

Section		Page
7.1	Thermoluminescent Dosimeters	7.1-1

*Intentionally Left Blank*

## 7.1 THERMOLUMINESCENT DOSIMETERS (TLDs)

<b>DQO START DATE</b>	January 1, 2004
<b>IMPLEMENTATION DATE</b>	January 1, 2025
<b>POINT OF CONTACT</b>	Tim Welty (631) 344-4212

### SUMMARY OF PROPOSED CHANGES

One off-site thermoluminescent dosimeter (TLD) was taken out of service in calendar year (CY) 2024 due to retirement. One off-site location will be sought in early 2025 to maintain full, 16-sector TLD coverage off site around BNL.

### DESCRIPTION AND TECHNICAL BASIS

The regulatory dose limit set by the Department of Energy (DOE) for members of the public is an effective dose equivalent (EDE) of 100 mrem (1mSv) in a year from all DOE activities via all environmental pathways. The Environmental Protection Agency (EPA) dose limit for airborne emissions under the Clean Air Act (CAA) for members of the public is 10 mrem (0.1 mSv) in a year via the inhalation and immersion pathways. The EDE includes the deep dose equivalent from yearly exposures to radiation sources external to the body (measured with TLDs), plus the committed effective dose equivalent from radionuclides taken into the body (e.g., inhalation, ingestion, and skin absorption).

Brookhaven National Laboratory (BNL) measures environmental background radiation through a network of on- and off-site TLDs suspended approximately one meter above the ground. These devices measure direct, penetrating beta/gamma radiation originating from cosmic and terrestrial sources, as well as any contribution from Laboratory operations. The off-site exposures are assumed to be true natural background doses with no contribution from Laboratory operations. On-site and off-site external doses are compared with each other statistically to estimate the contribution, if any, from BNL operations above the natural background level of radiation.

The scientific principle on which TLDs function is that when certain crystals contained in the TLD holder are exposed to penetrating gamma or neutron radiation, the impurities in the crystals' low-temperature trapping sites for electrons are excited to higher energy states proportional to the dose received. These electrons remain in a high-energy state at normal ambient temperatures. The crystals are then heated in a controlled manner to release, measure, and record the stored energy, which is called "processing".

The processing of TLDs by the BNL Personnel Monitoring Group consists of three phases. First, the TLD card is heated, causing the electrons to be released from the trapping sites and dropped to a lower energy state, which results in the emission of photons in the form of visible light; the intensity of emitted light is proportional to the original absorbed dose of radiation. Next, the light photons are measured with a photomultiplier tube and the light intensity measurement is recorded. Finally, after the TLD is read, the TLD is heated and read a second time for any residual dose to ascertain that all the gamma radiation-induced stored energy has been released, referred to as "annealing." This verifies that the TLD is ready for re-use in the field.

The environmental TLDs used at BNL are composed of calcium fluoride (CaF<sub>2</sub>: Dy) doped with Dysprosium or lithium fluoride (LiF: Mg, Ti) doped with magnesium titanium. The accuracy of

the TLD is verified using sources of known radiation exposure rates. For quality control, the Laboratory also participates in inter-comparison programs with other sites. The Personnel Monitoring Group in the Radiological Control Division processes environmental TLDs at BNL. The DOE Laboratory Accreditation Program accredits that laboratory operation.

The TLD used for neutron measurements at BNL is the Harshaw badge model 8814, which contains the neutron chip for measurement. Personnel Monitoring supplies and reads the TLDs after exposure, and subsequently reports the results to the Radioactive Airborne Emissions Subject Matter Expert on a quarterly basis.

## DRIVERS FOR MONITORING BEING CONDUCTED UNDER THIS CHANGE

- ☐ Compliance
- ☒ Support Compliance
- ☒ Surveillance
- ☐ Restoration

## DATA QUALITY OBJECTIVE ANALYSIS

This document was developed based on the EPA's Data Quality Objective (DQO) process. The DQO process is used to clarify objectives, define the type of data, and specify levels of potential decision errors that will be used as the basis for establishing the quality and quantity of data needed to support decision-making.

### Step 1: State the Problem

Radioactive materials and/or airborne emissions sources can contribute to ambient radiation levels. These sources include routine facility emissions and effluents, equipment and machines that generate radiation, environmental restoration activities, and on-site vehicle transport of sources or radioactive wastes. The environmental air and surface water pathways may also transport radionuclides from emission or effluent sources (point or diffuse) to locations near the public and/or terrestrial and aquatic biota. Many of these released radionuclides produce penetrating particles and photons (i.e., beta and gamma radiation) during decay processes in media that are external to an organism. This external radiation must be monitored to minimize exposure and demonstrate compliance with regulatory limits.

### Step 2: Identify the Decision

The primary decision to be made using data from direct radiation monitoring is whether the dose, if any, to members of the public originates from BNL sources and, if so, whether the dose is below the regulatory dose limits set by DOE and EPA. The following questions are considered in support of the decision-making:

- Are the external exposure measurements that were taken at locations with public or non-involved worker access higher than historical measurements and survey results?
- Is the dose below the regulatory compliance limits set by EPA and DOE?
- Are the site perimeter external doses reasonable and in the range of natural background?
- Is the potential dose to members of the public from the external dose pathway as low as reasonably achievable?
- Is the radiation exposure near specific facilities or waste sites contributing to the cumulative dose?
- Are all emission/source terms taken into consideration during placement of TLDs?

- Does the placement of background TLDs accurately portray background levels of radiation?
- What is the dose contribution from thermal neutrons?

### Step 3: Identify Inputs to the Decision

Currently, 63 environmental TLDs are deployed on the BNL site and 16 TLD's are deployed off site. An additional 30 control TLDs are stored in a lead-shielded container in Building 490. The average dose of the control TLDs is reported annually in the annual BNL Site Environmental Report as a reference dose measure labeled "075-TLD4."

The primary purpose of monitoring direct radiation is to measure the dose, if any, to members of the public from gamma radiation sources at BNL. The main objectives are to:

- Obtain ambient external dose measurements from potential sources at the BNL site;
- Obtain ambient external background dose measurements from full-occupancy, off-site locations inhabited by members of the public and uninvolved workers;
- Verify that the potential dose to members of the public from external pathways remains as low as reasonably achievable (the ALARA principle);
- Obtain radiation exposure data near facilities with radiation-generating machines or equipment and near radioactive waste sites to assess the integrated effect of the operations on overall exposures;
- Obtain dose measurements at the site perimeter and adjacent communities to ensure that external exposure from BNL operations is known at various distances and to confirm that exposure is in the range of background levels;
- Measure on- and off-site external radiation exposures to assess the environmental dose from unplanned releases, if any, and for comparison/assessment purposes;
- Document and maintain a record of exposure to show compliance with DOE and EPA dose limits.

At present, on- and off-site areas are divided into grids and the TLD numbers are assigned based on these grids. For more detailed information, refer to Environmental Monitoring Standard Operating Procedure (EM-SOP-202), *Sample Location Identification*.

As part of a voluntary program implemented by BNL employees, 16 TLDs are placed off site, nominally with one in each of all 16 wind sectors to monitor background dose levels. The placement of TLDs in these 16 off-site locations provides dose measurement which surrounds the Lab site.

Some facilities on the BNL site have the potential to generate high energy neutrons ranging from 0.025eV to >100 MeV. The Lab's Alternating Gradient Synchrotron (AGS) accelerates protons to energies up to 30GeV and heavy ion beams to 15 GeV/amu. The Relativistic Heavy Ion Collider (RHIC) has two beams circulating in opposite directions and can accept either protons or heavy ions up to gold. Protons are accelerated up to a final energy of 250 GeV and gold ions to 100 GeV per nucleon. Passive monitoring devices for neutrons provide retrospective indication of any change in radiological conditions to protect the environment and residents within the BNL vicinity. Therefore, to confirm and ascertain that there is no neutron dose contribution to the public, 11 pairs of neutron TLDs are placed near the Laboratory boundary on the west side.

Important factors that have influenced the decision to keep the TLD locations largely the same (in alignment with the previous regime) were the capability to look at the long-term trend analysis from previously collected historical data, the comparability of the recent TLD data with the enormous quantity of baseline data, the population distribution around the site, the site-specific meteorological conditions, and the recreational activities of the community adjacent to the site.

The types of radiation causing most of the external exposures are gamma photons and beta particles. Because the site is large and there are no longer any large-scale potential sources such as reactors, the maximum predicted exposure or concentration would typically be to on-site receptors rather than off-site receptors. Historical data support the approach of designing the measurement methods mainly for photon sources, but pure beta emitters can exist in the environment unaccompanied by gamma emitters (e.g., strontium-90). The following inputs are required to support decision-making based on TLD data:

- Analytical results are reviewed by project managers in accordance with EPD data review procedures to ensure data is of acceptable quality;
- TLD doses measured at BNL monitoring locations are compared to both recent and historical background measurements to determine the contribution, if any, from BNL operations;
- TLD doses measured at off-site monitoring locations are compared to both recent and historical background measurements to spot long-term trends in the data;
- Dose contributions from neutron TLDs are evaluated;
- TLDs are read, annealed, and reported by the Personnel Monitoring Group within BNL's Radiological Control Division;
- TLDs undergo a Cs-137 relative response test annually with sources traceable to the National Institute for Standards and Technology;
- Environmental TLDs are exchanged quarterly and read using Harshaw TLD readers and associated EM-SOPs and quality control;
- The dose units are reported in rem/day or rem/quarter with the number of exposure days documented in the report prepared by the Personnel Monitoring Group;
- The Personnel Monitoring Group corrects the TLD measurements for any residual dose found during the annealing process;
- Processing (annealing, calibration, reading, and testing) of the environmental dosimeters is done in accordance with the American National Standards Institute (ANSI) N13.29 standard.

#### **Step 4: Define the Study Boundaries**

The frequency for exchanging TLDs deployed in the field is determined on the basis of the potential for detecting external radiation levels above natural background radiation and the characteristics of the crystal used in the TLDs. For the environmental TLDs in use on site, a quarterly exchange frequency is considered optimal (so “fading” is minimal). This interval was determined to be the approximate exposure time needed to generate statistically distinguishable results.

External radiation is measured with consideration for the types and levels of exposure expected from the various pathways, transport media, and other direct radiation sources. Examples of critical environmental media or sources that present the potential for external radiation exposure are airborne cloud passage and exposure to contaminated surface water, vegetation, sediment, or soil. Regulatory dose limits have not changed and the burden to show regulatory compliance with ALARA limits continues to be required of BNL's environmental surveillance program. At present, the major facilities at the Laboratory that can contribute to ambient external exposure are the Brookhaven LINAC Isotope Producer (BLIP), the AGS, the Tandem Van de Graaff, the Booster Storage Ring, RHIC, the Former Waste Management Facility (FWMF), the Radionuclide Research and Production Laboratory, and the National Synchrotron Light Source II (NSLS-II). NSLS-II increased beam current from 400 mA to 500 mA several times in CY 2024. There may be more operation time at 500 mA in CY2025 than CY2024.

In an accelerator environment (e.g., AGS, RHIC), when a high-energy charged particle leaves the vacuum confines of the accelerator, nuclear fragments may be produced along the path of the energy particle or when it collides with other matter. TLD locations are selected near the

accelerators to fulfill the surveillance objectives. Also, the radioactive source information is used to determine the potential locations for placement of TLDs and the timely detection of exposures, if any. One facility known to release airborne gaseous products, and therefore is significant from an environmental monitoring point of view, is the BLIP facility.

Meteorological factors also play a part in the selection of TLD locations. At BNL, the ground-level winds are from the southwest during the summer, from the northwest in the winter, and with equal frequency from these two directions during the spring and fall. There is an ongoing need for dosimeters that provide background monitoring for public assurance, as well as dosimeters that would only be used in emergencies, to confirm emission controls or for dose modeling. Fulfilling these needs requires TLD placement in off-site locations that are generally upwind (for the background locations) and in population centers located downwind from the laboratory in the prevailing wind directions.

Of the 63 TLDs on site, 36 were posted at natural background locations within the BNL site boundary for comparison with the off-site TLDs (Table 7.1-1 below).

**Table 7.1.1. Ambient Background TLD Locations at BNL**

<b>TLD Number</b>	<b>Location</b>	<b>Rationale for Placement</b>
011-TLD1	North Firebreak	Measure natural background dose
013-TLD1	North Firebreak	Measure natural background dose
030-TLD1	NE Firebreak	Measure natural background dose
037-TLD1	S-13	Measure natural background dose
043-TLD1	North Access Road	Measure natural background dose
043-TLD2	North of Meteorology Tower	Measure natural background dose
049-TLD1	East Firebreak	Measure natural background dose
053-TLD1	West Firebreak	Measure natural background dose
055-TLD1	Fence - Thomson & Fifth	Measure natural background dose
055-TLD2	Bldg. 935 Notice Shelter	Measure natural background dose
063-TLD1	West Firebreak	Measure natural background dose
065-TLD1	Fence – Bldg. 820	Measure natural background dose
066-TLD1	Waste Management Facility	Measure natural background dose
073-TLD1	Meteorology Tower	Measure natural background dose
080-TLD1	East Firebreak	Measure natural background dose
082-TLD1	West Firebreak	Measure natural background dose
084-TLD1	Tennis Court	Measure natural background dose
085-TLD1	Building 735	Measure natural background dose
085-TLD2	Upton Gas Station	Measure natural background dose
085-TLD3	NSLS-II LOB 745	Measure natural background dose
086-TLD1	Baseball Fields	Measure natural background dose
086-TLD2	NSLS-II LOB 741	Measure natural background dose
086-TLD3	NSLS-II LOB 742	Measure natural background dose
090-TLD1	North St. Gate	Measure natural background dose
095-TLD1	NSLS-II LOB 744	Measure natural background dose
096-TLD1	NSLS-II LOB 743	Measure natural background dose
105-TLD1	South Firebreak	Measure natural background dose
108-TLD1	Water Tower	Measure natural background dose
108-TLD2	Tritium Pole	Measure natural background dose
111-TLD1	Trailer Park	Measure natural background dose
122-TLD1	South Firebreak	Measure natural background dose
126-TLD1	South Gate	Measure natural background dose
P-2, P-4, P-7, and S-5	Perimeter Blockhouses	Measure natural background dose and compare with historical data

The remaining on-site TLDs are posted at various facility monitoring locations and are categorized as Facility Area Monitors (FAM). The FAM dosimeters are deployed in locations where there are known sources of potentially higher external radiation dose, such as the sky shine phenomenon, possible beam loss, loss of shielding, or near beam stops. These dosimeters do not represent the true environment background

dose but could have elevated dose contributions from operations, any of the above-stated causes, or from an emergency scenario. If data from the FAM dosimeters were used to calculate the annual on-site average dose, the value would be inflated and incorrect. The primary purpose of the FAM TLDs is to measure and monitor dose due to known sources or to unplanned releases.

Five TLDs are in the vicinity of the AGS to monitor the ambient external dose rates in that area (Table 7.1.2).

**Table 7.1.2. AGS TLD Locations**

<b>TLD Number</b>	<b>Location</b>	<b>Rationale for Placement</b>
074-TLD1	Bldg. 560	Occupied area/background
074-TLD2	Bldg. 907	Occupied area/background
054-TLD1	Bldg. 914	Beam stop/Sky shine
054-TLD2	Northeast of Bldg. 913B	Beam stop/Sky shine
054-TLD3	Northwest of Bldg. 913B	Beam stop/Sky shine

Radiation external to the RHIC tunnel is generated by facility operations. The radiation field consists mainly of neutrons, muons, and gamma radiation. The beam stops are expected to account for 85 percent of the total beam loss energy. Fifteen TLDs are deployed near the RHIC Ring, beam stops, and occupied buildings (Table 7.1-3).

**Table 7.1.3. RHIC TLD Locations**

<b>TLD Number</b>	<b>Location</b>	<b>Rationale for Placement</b>
025-TLD1	Bldg. 1010 Beam Stop 1	Beam Stop/shielding
025-TLD4	Bldg. 1010 Beam Stop 4	Beam Stop/Shielding
027-TLD1	South of Bldg. 1002A	Occupied areas/study
027-TLD2	East of Bldg. 1002D	Occupied areas/study
034-TLD2	Bldg. 1008 Collimator 4	Beam Collimator
036-TLD1	East side of Bldg. 1004B	Occupied area/study
036-TLD2	East corner of 1004	Occupied area
044-TLD1	Bldg. 1006	Occupied area
044-TLD2	South of Bldg. 100E	Occupied area
044-TLD3	South of Bldg. 1000P	Occupied area
044-TLD5	North of Bldg. 1000P	Occupied area
045-TLD1	Bldg. 1005S	Occupied area
045-TLD2	East of Bldg. 1005S	Occupied area
045-TLD4	SW of Bldg. 1005S	Occupied area
045-TLD5	WSW of Bldg. 1005S	Occupied area

Data from the S-6 location near the FWMF, together with previously collected TLD external dose data, suggests that there are radiation sources near the S-6 blockhouse location. The potential sources in this area could be contaminated materials stored within the fenced area, materials being repackaged for disposal at an off-site licensed location, or contaminated media (e.g., soils). To investigate the extent of contamination as well as the external dose rate at this location, four additional TLDs (088-TLD1 through 088-TLD4) are posted at the S-6 ambient air sampling location, equidistant from each other, on the enclosure fence of the FWMF.

Building 356 houses one Cobalt-60 source, one Am-Be source, and five small Californium-252 sources. This building is being monitored because previous TLD readings were higher than the natural background dose. The original TLD (075-TLD3) has been supplemented with an additional TLD, 075- TLD5, which is located at the corner of Building 356 to record the dose rate.

Twelve TLD pairs that contain the neutron chip were posted in 2010 to evaluate neutron dose from the AGS and RHIC facilities (Table 7.1-4). As mentioned earlier, one pair was converted to a pair of environmental TLDs and moved to the NSLS-II in the third quarter of 2017; eleven TLD pairs remain.



Table 7.1.4. Neutron TLD Locations

TLD#	Location	Rational for Placement
025-TLD-N2	Bldg. 1010 Beam Stop	Beam Stop/shielding
034-TLD-N1	Bldg. 1008 Collimator	Beam Collimator
034-TLD-N2	Bldg. 1008 Collimator	Beam Collimator
043-TLD-N1	Upton Road/North Gate	Occupied Area
043-TLD-N2	White Pine Path/Canopy Road	Proximity to Site Boundary
042-TLD-N1	RHIC W-line Beam Stop	Beam Stop/Shielding
042-TLD-N2	West 5 <sup>th</sup> /Canopy Road	Proximity to Site Boundary
054-TLD-N1	J-10 beam Stop	Beam Stop/Shielding
054-TLD-N2	LINAC to Booster transition (EBIS)	Beam Stop/Shielding
054-TLD-N3	BLIP Area	Soil Activation
064-TLD-N1	Booster Stop	Beam Stop/Shielding

### Step 5: Develop the Decision Rules

The annual BNL Site Environmental Report shall be used as the reporting method and as a record of dose for members of the public. **If** the annual average dose for an off-site TLD is statistically outside the range of 60 to 76 mrem at the  $2\sigma$  confidence interval, **then** an investigation into the cause of higher/lower dose at the off-site location would be performed. **If** the annual dose for on-site TLDs is statistically outside the range of 66 to 85 mrem at the  $2\sigma$  confidence interval, **then** an investigation into the cause of higher/lower dose at the on-site location would be performed and corrective action taken to reduce the dose to normal background levels.

Perform a statistical test to determine whether the variability in the on-site, off-site, and natural background exposures is statistically different. **If** the variability is higher than normal (based on historical data), **then** notify the facility manager of the need to implement corrective actions. **If** the TLD readings continue to remain above normal background, **then** access to radiological areas may be restricted, radiological postings may be necessary, or other corrective actions will be taken. The Radiological Control Division Manager and the Environmental Protection Division Manager shall be informed about the above-background exposure rate at the facility or area. **If** a TLD is missing, **then** the annual dose is calculated as four times the average quarterly dose, determined from available data. **If** TLDs are wet, damaged, or found on the ground, **then** they are not accepted for use in reporting monitoring data. **If** an unplanned release occurs, **then** the TLDs in the upwind and downwind directions shall be immediately retrieved and processed to estimate the dose to members of the public. **If** intermittent or sporadic operations have a significant potential for elevating environmental exposures, **then** survey frequencies shall be increased. **If** the quality control program does meet the ANSI standard, **then** the dose data shall be evaluated for usability and reportability.

### Step 6: Specify Acceptable Error Tolerances

The TLD readings' arithmetical average, normalized to 365 days, would be acceptable at  $72 \pm 8$  mrem/year at  $2\sigma$ . Sampling frequencies for on-site TLDs may require adjustments to reflect changes, such as the potential for elevated exposure rates due to modifications in operations or the transportation of radiation sources.

### Step 7: Optimize the Design

The TLD data are evaluated on a quarterly basis to upgrade the monitoring program until dose rates are at normal background levels or until a radiological boundary sign is posted. BNL's personnel dosimetry program undergoes the DOE Laboratory Accreditation Program evaluation every two years and must meet specified inter-laboratory comparison performance goals. The accreditation program is specifically for dosimeters worn by personnel to monitor the dose they receive. Although no comparable DOE accreditation program exists for environmental monitoring, the Laboratory has participated in the field testing of a proposed comparable program and has incorporated the key features of that program into the

BNL environmental dosimetry program.

The quality control features in this program are:

- Calibration, maintenance, and audits of the TLD reading/recording system
- Anomalous data evaluation
- Personnel training
- Procedures and records maintenance

The quality control program within the Personnel Monitoring group maintains routine quality control of the TLD process cycle. The quality control program provides a measure of the quality of the complete TLD processing cycle. Inter-comparison studies are conducted to determine and document TLD processing performance.

Anomalous TLD results are evaluated promptly to confirm or dismiss them. Investigation into an anomalous result includes, as necessary, verification of the quality of the result (sampling and analytical aspects), questioning staff at facilities near the location with anomalous results about unusual situations, reviewing nearby air sampling results, and following up with immediate portable instrument measurements and/or gamma spectroscopy.

The TLDs are handled carefully during transport to keep them away from significant external radiation fields that would generate false positive data. Comments describing any unusual handling of TLDs or any findings that may affect TLD results are recorded in the BNL Field Sampling Team's field notebook. Sample collection and handling procedures are documented in EM-SOP 502, *Placement and Collection of Thermoluminescent Dosimeters*.

See Appendix B for the monitoring program for this DQO.